

ShaoGuan Rising Novel Material Technology CO., LTD

Address: No.2, Pingan East Road 2, Zhuji Industrial parks, Nanxiong City, Guangdong Province, P.R. China.

Telephone Number: +86-751-3867118, +86-751-3867117, +86-751-3867116

Emergency Number: +86-751-3867128(Miss Zhong)

RA7628

1. Chemical names: Hydroxyl Acrylic Resin

2.Description: High solid contents; high gloss, nice film build, moderate drying speed, convenient for coating operation, nice leveling.

3. Typrical properties:

Test Item	Standard	Test condition
Appearance	Colorless to light yellow liquid	Vision
Color	≤1	Iron, cobalt colorimeter
Solid content	70±2%	150°C baking 1 hours
Acid value	8-12	mgKOH/g
Viscosity	4000-10000 cps/25°C	NDJ-1 rotating viscometer
OH value	92	The theoretical value
Solvent	XYL/BAC	

4.Application: Coating for automobile original finish and refinish, coating for machine, high solids PU topcoat and clear coating on metal and plastics.

5.solvent dilution: This product is available aromatic hydrocarbons, esters, ketones, ethers solvent dilution, the stability of please test when using resin in solvent and solvent effects on film.

6. Packing: 200kg/drum,20 kg/drum. The product is able to be kept for one year at regular temperature in sealed pack and dark condition. When kept for above 12 months, product retesting is suggested before application.

Noted: The information contained herein is offered in good faith and is believed to be accurate. However, because the measurement method and condition of the product is limited by our control on quality, so the information should not be used in substitution for customer's a test to ensure that our products are safe, effective, and fully satisfactory for the intended to ending use.